

Electric strike 34- - - - - E91

Without striking plate, 12 V DC

Product description

Model with basic equipment.

Overview of Advantages

- Suitable for all common striking plates
- Can be combined with striking plates with latch bolt guide (standard) without FaFix®
- Due to 180° fitting, can be used DIN right and left
- Latch material: Steel

Scope of delivery

- 1 piece electric strike

Note

- Order code for version DIN right = 34A

Technical data

Dimensions	Depth: 28 mm , Height: 90 mm , Width: 20 mm
Version	Standard electric strikes
Latch version	Standard latch
Mounting	asymmetrical
With fixing	No
Waterproof	No
Mounting method	Installation
Type of current	DC
How they work	Fail-unlocked
Pulse contact	Yes
Unlocking type	Standard version
Permanent operation (100% power-on time)	Yes
Mechanical unlocking	No
Suitable for smoke protection door	No
Max. latch preload DC	0 N
Min. preload DC	10 N
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	No
Mechanical noise damping	No
Drill hole offset by 1 mm	No
Unlock period	0.1 s
Operating temperature range	-15-40 °C
Suitable for fire door	No
Installation position	universal
With feedback signal	No
Opening direction according to DIN	left/right
Adjustable keeper- FaFix	No
Adjustable electric strike – Fix	No
Adjustable strike plate	No
Latch bolt guide integrated – Profix	No
For strike plates with latch bolt guide	No
Mechanical stability (no burglary resistance)	5500 N
Protective diode	No
Voltage	12 V
Max. current consumption DC	195 mA
Continuous duty	11-13 V
Nominal resistance 12 V	61 Ohm
Nominal operating voltage tolerance	+ - 1 V

Article number	34-----E91
EAN	4042203148260

