



Model with mechanical unlocking.

Overview of Advantages

- Suitable for all common striking plates
- Due to 180° fitting, can be used DIN right and left
- Symmetrical design

Technical data	
Voltage	8-16 V AC/DC
DIN direction	Universal
Adjustable latch (FF, FaFix®)	Yes
Mechanical unlocking (E)	Yes
Fail-locked	Yes
Hold-open function	Yes
Break-in resistance	3500 N
Height	75 mm
Width	20,5 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Operating voltage tolerance range 8 V	as specified
Rated operating voltage tolerance range	as specified
Operating voltage tolerance range 12 V	as specified
Operating voltage tolerance range 16 V	as specified
Rated resistance 8 V	22 Ω
Nominal resistance 12 V	22 Ω
Rated resistance 16 V	22 Ω
AC-current consumption 8 V	310 mA
AC current consumption 12 V	470 mA
AC-current consumption 16 V	620 mA
DC-current consumption (50% Residual ripple) 8 V	350 mA
DC-current consumption (50% Residual ripple) 12 V	520 mA
DC-current consumption (50% Residual ripple) 16 V	690 mA
DC-current consumption (stabilized) 8 V	360 mA
DC-current consumption (stabilized) 12 V	550 mA
DC-current consumption (stabilized) 16 V	730 mA
Max. latch preload AC operation 8 V	60 N
Max. latch preload AC operation 12 V	150 N
Max. latch preload AC operation 16 V	150 N
Max. keep pre-load DC (50% Residual ripple) 8 V	80 N
Max. latch preload DC (50% ripple) 12 V	50 N
Max. latch preload DC (50% ripple) 16 V	50 N
Max. latch preload DC (stabilised) 8 V	50 N
Max. latch preload DC (stabilised) 12 V	10 N
Max. latch preload DC (stabilised) 16 V	10 N
EAN-Number	Article number
	E7AE-----R11